


| | | LS1000A(TH) Series(Totem) / SERIE LS1000(TH)Totem | | |
|---|--|--|--|----------------|
| | | 43 in/pollici LS1000A (TH) | 49LS1000A (TH) | 55LS1000A (TH) |
| | |  | | |
| Panel Parameters Parametri display | Touched Screen | Yes | | |
| | Technology | IR(10 POINTS) | | |
| | Resolution | 1920*1080 | | |
| | Screen Ratio | 16: 9 | | |
| | Visual Angle | 85/85/85/85 | | |
| | Refresh frequency | 60Hz | 60Hz | 60Hz |
| | Life Time | 30000H | 30000H | 30000H |
| | Static contrast ratio | 1000:1 | 2000:1 | 2000:1 |
| | Response speed | 8ms | 8ms | 8ms |
| | Max Brightness | 350cd/m ² | | |
| Core Parameters Parametri processore | Chip | RK3288;Quad-core Cortex-A17\Dominant frequency1.8GHz | | |
| | OS | Android 5.1 | | |
| | CPU | Quad-core Cortex-A17 | | |
| | System memory | 2G DDR3 | | |
| | Hard disk storage | 8G | | |
| Interface Setting Impostazioni interfaccia | USB2.0 | 1 | | |
| | USB3.0 | NA | | |
| | Earphone | 1 | | |
| | LAN | 1 | | |
| | TF Cassette | 1 | | |
| | HDMI 2.0 | NA | | |
| Basic functions Funzioni base | Horizontal and vertical display | / | / | / |
| | Timing switch | yes | yes | yes |
| | USB data input | yes | yes | yes |
| | Cable network | yes | yes | yes |
| | Wireless Wi-Fi | yes | yes | yes |
| | Speaker Power | 2*5W | 2*5W | 2*5W |
| | Quantity of speaker | 2 | 2 | 2 |
| | Interactive Device Supporto interattivo | Media Info Display | Support videos splitting, subtitle rolling, switch timing and USB data input | |
| Release System in Background (Option) | | Support Program management/ Terminal management/ News making/ Program making | | |
| Video Decoding | | 3GP, 3G2, AVI,FLV,F4V,OGG,MP4,MOV,TS,M2TS,M2T,M2P,MKV,etc. | | |
| Picture Format | | Support Android standard picture forma, including: jpeg, png, gif, bmp and etc. | | |
| CBU Craft Telaio | CBU material | Metal/ aluminum | | |
| | Frame material | aluminum | | |
| | CBU color | Black | Black | Black |
| | Frame color | Silver | Silver | Silver |
| | Frame Size | 58mm | 58mm | 58mm |
| | CBU Thickness | 89.3mm | 91.9mm | 94.1mm |
| | Distance Between Installing Holes | No | | |
| | Quantity of Installing Holes | | | |
| Power | Rated Power Consumption | 85W | 110W | 160W |